

## Surface Mount Schottky Barrier Rectifier

Reverse Voltage - 20 to 200 V

Forward Current - 1 A


### FEATURES

- ◆Metal silicon junction, majority carrier conduction
- ◆For surface mounted applications
- ◆Low power loss, high efficiency
- ◆High forward surge current capability
- ◆For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ◆Lead free in comply with EU RoHS 2011/65/EU directives

### MECHANICAL DATA

- ◆Case: SMAF
- ◆Terminals: Solderable per MIL-STD-750, Method 2026
- ◆Approx. Weight: 27mg / 0.00095oz

### Pinning



### Marking Code

|               |                  |
|---------------|------------------|
| <b>SS12F</b>  | <b>YFW SS12</b>  |
| <b>SS14F</b>  | <b>YFW SS14</b>  |
| <b>SS16F</b>  | <b>YFW SS16</b>  |
| <b>SS18F</b>  | <b>YFW SS18</b>  |
| <b>SS110F</b> | <b>YFW SS110</b> |
| <b>SS112F</b> | <b>YFW SS112</b> |
| <b>SS115F</b> | <b>YFW SS115</b> |
| <b>SS120F</b> | <b>YFW SS120</b> |

#### Absolute Maximum Ratings and Electrical characteristics


Ratings at 25 ° ambient temperature unless otherwise specified.Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

| Parameter  | Symbols         | SS12F      | SS14F | SS16F | SS18F | SS110F   | SS112F | SS115F   | SS120F | Units |
|--|-----------------|------------|-------|-------|-------|----------|--------|----------|--------|-------|
| Maximum Repetitive Peak Reverse Voltage  | $V_{RRM}$       | 20         | 40    | 60    | 80    | 100      | 120    | 150      | 200    | V     |
| Maximum RMS voltage  | $V_{RMS}$       | 14         | 28    | 42    | 56    | 70       | 84     | 105      | 140    | V     |
| Maximum DC Blocking Voltage  | $V_{DC}$        | 20         | 40    | 60    | 80    | 100      | 120    | 150      | 200    | V     |
| Maximum Average Forward Rectified Current  | $I_{F(AV)}$     | 1.0        |       |       |       |          |        |          |        | A     |
| Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed On Rated Load (JEDEC method)  | $I_{FSM}$       | 40         |       |       |       | 30       |        |          |        | A     |
| Maximum Instantaneous Forward Voltage at 1 A   | $V_F$           | 0.55       |       | 0.70  |       | 0.85     |        | 0.90     |        | V     |
| Maximum Instantaneous Reverse Current at Rated DC Reverse Voltage<br><small><math>T_A = 25^{\circ}C</math><br/><math>T_A = 100^{\circ}C</math></small> | $I_R$           | 0.3<br>10  |       |       |       | 0.2<br>5 |        | 0.1<br>2 |        | mA    |
| Typical Junction Capacitance <sup>(1)</sup>  | $C_j$           | 110        |       |       | 80    |          |        |          |        | pF    |
| Typical Thermal Resistance <sup>(2)</sup>  | $R_{\theta JA}$ | 95         |       |       |       |          |        |          |        | °C/W  |
| Operating Junction Temperature Range   | $T_j$           | -55 ~ +150 |       |       |       |          |        |          |        | °C    |
| Storage Temperature Range  | $T_{stg}$       | -55 ~ +150 |       |       |       |          |        |          |        | °C    |


(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(2) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Reverse Characteristics**




**Fig.3 Typical Forward Characteristic**




**Fig.4 Typical Junction Capacitance**



**Fig.5 Maximum Non-Repetitive Peak Forward Surge Current**



**Fig.6- Typical Transient Thermal Impedance**



**Marking Diagram**



**Ordering information**


| Package | Packing Description | Packing Quantity               |
|---------|---------------------|--------------------------------|
| SMAF    | Tape/Reel, 13" reel | 10000PCS/Reel 100000PCS/Carton |
|         | Tape/Reel, 7" reel  | 3000PCS/Reel 120000PCS/Carton  |

**Package Dimensions**

**SMAF**

| Dim. | Millimeter(mm) |      | mil  |      |
|------|----------------|------|------|------|
|      | Min.           | Max. | Min. | Max. |
| A    | 0.9            | 1.1  | 35   | 43   |
| C    | 0.12           | 0.20 | 4.7  | 7.9  |
| D    | 3.3            | 3.7  | 130  | 146  |
| E    | 2.4            | 2.7  | 94   | 106  |
| e    | 1.3            | 1.6  | 51   | 63   |
| g    | 0.8            | 1.2  | 31   | 47   |
| HE   | 4.4            | 4.9  | 173  | 193  |
| ∠    | 7°             |      |      |      |

**The recommended mounting pad size**



## Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.