

**35A HIGH CURRENT SINGLE-PHASE
SILICON BRIDGE RECTIFIER**

Voltage - 600 to 1600 V


Forward Current – 35 A

FEATURES

- ◆High current capability
- ◆Low forward voltage drop
- ◆Glass Passivated Chip Junction
- ◆Low power loss, high efficiency
- ◆Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

- ◆Case: KBPC, KBPC-W
- ◆Terminals: Solderable per MIL-STD-202, Method 208
- ◆Approx. Weight: KBPC 31.6g , KBPC-W 28.5g



Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Parameter	Symbols	KBPC3506 (W)	KBPC3508 (W)	KBPC3510 (W)	KBPC3512 (W)	KBPC3516 (W)	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	600	800	1000	1200	1600	V
Maximum RMS voltage	V_{RMS}	420	560	700	840	980	V
Maximum DC Blocking Voltage	V_{DC}	600	800	1000	1200	1600	V
Maximum Average Forward Rectified Current at TC=60°C	$I_{(AV)}$	35					A
Peak Forward Surge Current 8.3 ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	400					A
Maximum Forward Voltage at 17.5A DC and 25°C	V_F	1.1					V
Maximum Reverse Current at TA=25°C at Rated DC Blocking Voltage TA=125°C	I_R	10 1.0					μA mA
Operating and Storage Temperature Range	T_j, T_{stg}	-55 ~ +150					°C

(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(2) Thermal Resistance Junction to Case, Lead and Ambient.

Ratings And Characteristic Curves

FIG.1-MAXIMUM FORWARD SURGE CURRENT




FIG.2- DERATING CURVE
OUTPUT RECTIFIED CURRENT




FIG.3-TYPICAL FORWARD
CHARACTERISTICS
KBPC35






FIG.4-TYPICAL REVERSE
CHARACTERISTICS



Marking Diagram



Ordering information


Package	Packing Description	Packing Quantity
KBPC	bulk	50PCS/Box 500PCS/Carton

Package Dimensions

KBPC

Dim.	Millimeter(mm)		Dimensions inInch	
	Min.	Max.	Min.	Max.
A	28.2	28.8	1.11	1.13
B	15.3	17.3	0.602	0.681
C	17.1	19.1	0.673	0.752
D	13.2	15.2	0.520	0.598
E	0.75	0.85	0.0295	0.0335
F	6.2	6.4	0.244	0.252
G	2.3	2.5	0.091	0.098
H	10.8	11.2	0.425	0.441
I	19	-	0.748	-

Marking Diagram



Ordering information

Package	Packing Description	Packing Quantity
KBPC-W	bulk	50PCS/Box 500PCS/Carton

Package Dimensions

KBPC-W

Dim.	Millimeter(mm)		Dimensions inInch	
	Min.	Max.	Min.	Max.
A	28.2	28.8	1.11	1.13
B	17.1	19.1	0.673	0.752
C	10.4	12.4	0.409	
D	0.95	1.05	0.037	0.041
E	10.8	11.2	0.425	0.441
F	30	-	1.18	-

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.