


General Purpose Diode
Reverse Voltage - 2000 V
Forward Current - 1 A
Features

- ◆The plastic package carries UL Flammability Classification 94V-0
- ◆For surface mounted applications
- ◆Low reverse leakage
- ◆Built-in strain relief, ideal for automated placement
- ◆High forward surge current capability
- ◆High temperature soldering guaranteed:260℃/10 seconds at terminals

Mechanical Characteristics

- ◆Case: SMA (DO-214AC) package molded plastic body over passivated chip
- ◆Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- ◆Polarity: Color band denotes cathode end
- ◆Mounting Position: Any

Pinning


Parameter		Symbols	EM520	Units
Maximum repetitive peak reverse voltage		V_{RRM}	2000	V
Maximum RMS voltage		V_{RMS}	1400	V
Maximum DC blocking voltage		V_{DC}	2000	V
Maximum average forward rectified current		I_{AV}	1	A
Peak forward surge current ^(NOTE1)		I_{FSM}	30	A
Maximum instantaneous forward voltage at 1A		V_F	1.1	V
Maximum DC reverse current at rated DC blocking voltage	$T_A=25\text{ }^{\circ}\text{C}$	I_R	5	uA
	$T_A=100\text{ }^{\circ}\text{C}$	I_{RT}	100	uA
Typical junction capacitance ^(NOTE 2)		C_J	15	pF
Typical Thermal Resistance Junction to Ambient ^(NOTE3)		$R_{\theta JA}$	85	°C/W
Typical Thermal Resistance Junction to Lead ^(NOTE3)		$R_{\theta JL}$	28	°C/W
Operating Temperature Range		T_J	-55 to 150	°C
Storage Temperature Range		T_{STG}	-55 to 150	°C

Note1: 8.3ms single half sine-wave superimposed on rated load

Note2: Measured at 1MHz and applied reverse voltage of 4.0V DC.

Note3: PCB. mounted with 5×5mm copper pad areas

Ratings And Characteristic Curves

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS





FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS



Marking Diagram



Ordering information


Package	Packing Description	Packing Quantity
DO-214AC SMA	Tape/Reel, 13" reel	5000PCS/Reel 50000PCS/Carton

Package Dimensions

DO-214AC SMA

Dim.	Millimeter(mm)		mil	
	Min.	Max.	Min.	Max.
A	1.9	2.45	75	96
D	4.0	4.5	157	181
E	2.5	2.8	100	110
H _E	4.7	5.2	185	205
c	0.15	0.31	6	12
e	1.3	1.8	51	71
g	0.9	1.5	35	59
b	0.05	0.2	2	7.9
a	0.3		12	

The recommended mounting pad size



Unit : $\frac{\text{mm}}{(\text{mil})}$

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.