

■ Switching Diodes

FEATURES

- ◆ For surface mounted applications
- ◆ Glass Passivated Chip Junction
- ◆ Fast reverse recovery time
- ◆ Ideal for automated placement
- ◆ Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

- ◆ Case: SOD-123
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026
- ◆ Approx. Weight: 16mg / 0.00056oz

Pinning

1.Cathode	2.Anode
	
SOD-123	

Marking Code

BAV19W	A8
BAV20W	T2
BAV21W	T3

Absolute Maximum Ratings at 25 °C

Parameter		Symbols	BAV19W	BAV20W	BAV21W	Units
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	120	200	250	V
Maximum RMS voltage		V_{RMS}	100	150	200	V
Continuous Forward Current		I_F	250			mA
Repetitive Peak Forward Current		I_{FRM}	625			mA
Non-reptitive Peak Forward Surge Current	at 1s	I_{FSM}	1			A
	at 1ms		3			
	at 1us		9			
Total Power Dissipation		P_{tot}	500			mW
Operating and Storage Temperature Range		T_j, T_{stg}	-55 ~ +150			°C

Characteristics at Ta = 25 °C

Parameter		Symbols	BAV19W	BAV20W	BAV21W	Units
Reverse BreakdownVoltage at IR=100μA		V _{(BR)R}	120	200	250	V
Maximum Forward Voltage	at 100 mA	V _F	1.00			V
	at 200 mA		1.25			
Maximum DC Reverse Current at Rated DC Blocking Voltage	T _a =25°C	I _R	0.1			uA
	T _a =150°C		100			
Typical Junction Capacitance at V _R =4V, f=1MHz		C _j	5			pF
Maximum Reverse Recovery Time		T _{rr}	50			nS

① Measured with $I_F = 0.5 A, I_R = 1 A, I_{rr} = 0.25 A$

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instaneous Forward Characteristics





Fig.4 Typical Junction Capacitance



Ordering information


Package	Packing Description	Packing Quantity
SOD-123	Tape/Reel, 7" reel	3000PCS/Reel 120000PCS/Carton

Package Dimensions

SOD-123

Dim.	Millimeter(mm)		mil	
	Min.	Max.	Min.	Max.
A	0.9	1.3	35	51
C	0.09	0.22	3.5	8.7
D	1.5	1.8	59	71
E	2.5	2.8	98	110
E1	3.6	3.9	142	154
b	0.5	0.7	20	28
L1	0.25	0.45	10	18
A1	-	0.2	-	8
∠	9°			

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.