


-100V P-CHANNEL ENHANCEMENT MODE MOSFET

MAIN CHARACTERISTICS

I_D	-30A
V_{DSS}	-100V
$R_{DS(on)-typ}(@V_{GS}=-10V)$	< -110mΩ (Type: 86 mΩ)

Application

- ◆ Battery protection
- ◆ Load switch
- ◆ Uninterruptible power supply



Maximum Ratings at $T_c=25^{\circ}\text{C}$ unless otherwise specified

Characteristics	Symbols	Value	Units
Drain-Source Voltage	V_{DS}	-100	V
Gate - Source Voltage	V_{GS}	± 20	V
Continuous Drain Current @ $T_c=25^{\circ}\text{C}$	I_D	-30	A
Continuous Drain Current @ $T_c=100^{\circ}\text{C}$	I_D	-16	A
Pulsed Drain Current ²	I_{DM}	-75	A
Single Pulse Avalanche Energy ³	E_{AS}	157.2	mJ
Avalanche Current	I_{AS}	25	A
Total Power Dissipation ⁴ @ $T_c=25^{\circ}\text{C}$	P_D	96	W
Storage Temperature Range	T_{STG}	-55 to +150	$^{\circ}\text{C}$
Operating Junction Temperature Range	T_J	-55 to +150	$^{\circ}\text{C}$
Thermal Resistance Junction-Ambient ¹	$R_{\theta JA}$	62	$^{\circ}\text{C/W}$
Thermal Resistance Junction to Case ¹	$R_{\theta JC}$	1.3	$^{\circ}\text{C/W}$

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=-250\mu A$	BV_{DSS}	-100	-	-	V
Static Drain-Source On-Resistance ²	$V_{GS}=-10V, I_D=-10A$	$R_{DS(ON)}$	-	78	95	mΩ
	$V_{GS}=-4.5V, I_D=-8A$		-	86	110	
Gate -Threshold Voltage	$V_{DS}=V_{GS}, I_D=-250\mu A$	$V_{GS(th)}$	-1.2	1.7	-2.5	V
Drain-Source Leakage Current	$V_{DS}=-100V, V_{GS}=0V, T_J=25^\circ C$	I_{DSS}	-	-	-50	μA
Gate -Source Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$	I_{GSS}	-	-	±100	nA
Forward Transconductance	$V_{DS}=-10V, I_D=-10A$	g_{fs}	-	24	-	S
Total Gate Charge	$V_{DS}=-50V$ $V_{GS}=-10V$ $I_D=-20A$	Q_g	-	44.5	-	nC
Gate-Source Charge		Q_{gs}	-	9.13	-	
Gate-Drain Charge		Q_{gd}	-	5.93	-	
Turn-on delay time	$V_{DD}=-50V$ $V_{GS}=-10V$ $I_D=-10A$ $R_G=3.3\Omega$	$t_{d(on)}$	-	12	-	ns
Rise Time		T_r	-	27.4	-	
Turn-Off Delay Time		$t_{d(OFF)}$	-	79	-	
Fall Time		t_f	-	53.6	-	
Input Capacitance	$V_{DS}=-20V$ $V_{GS}=0V$ $f=1MHz$	C_{iss}	-	3029	-	pF
Output Capacitance		C_{oss}	-	129	-	
Reverse Transfer Capacitance		C_{rss}	-	76	-	
Continuous Source Current ^{1,5}	$V_G=V_D=0V$, Force Current	I_S	-	-	-18	A
Diode Forward Voltage ²	$V_{GS}=0V, I_S=-1A, T_J=25^\circ C$	V_{SD}	-	-	-1.2	V
Reverse Recovery Time	$I_F=-8A, dI/dt=100A/\mu s, T_J=25^\circ C$	t_{rr}	-	38.7	-	ns
Reverse Recovery Charge		Q_{rr}	-	22.4	-	nC

Note :

- 1、The data tested by surface mounted on a 1 inch2 FR-4 board with 2OZ copper.
- 2、The data tested by pulsed , pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- 3、The EAS data shows Max. rating . The test condition is $V_{DD}=-72V, V_{GS}=-10V, L=0.1mH, I_{AS}=-25A$
- 4、The power dissipation is limited by 150°C junction temperature
- 5、The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation

Ratings and Characteristic Curves




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs G-S Voltage




Fig.3 Typical S-D Diode Forward Voltage




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs T_J




Fig.6 Normalized $R_{DS(on)}$ vs T_J

Ratings and Characteristic Curves




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform





Fig.11 Unclamped Inductive Waveform

Marking Diagram



Ordering information


Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFW30P10AT	TO-220AB	0.07oz(1.96g)	50pcs/tube	1000PCS/Box 5000PCS/Carton

Package Dimensions

TO-220AB

Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.30	4.70	0.169	0.185
A1	2.52	2.82	0.099	0.111
b	0.71	0.91	0.028	0.036
b1	1.17	1.37	0.046	0.054
c	0.30	0.50	0.012	0.020
c1	1.17	1.37	0.046	0.054
D	9.90	10.20	0.390	0.402
E	8.50	8.90	0.335	0.350
E1	12.00	12.50	0.472	0.492
e	2.44	2.64	0.096	0.104
e1	4.88	5.28	0.192	0.208
F	2.60	2.80	0.102	0.110
L	13.20	13.80	0.520	0.543
L1	3.80	4.20	0.150	0.165
Φ	3.60	3.96	0.142	0.156

Marking Diagram



Ordering information


Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFW30P10AF	TO-220F	0.06oz(1.74g)	50pcs/tube	1000PCS/Box 5000PCS/Carton

Package Dimensions

TO-220F

Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.50	4.90	0.177	0.193
A1	2.34	2.74	0.092	0.108
A2	2.66	2.86	0.105	0.113
b	0.75	0.85	0.030	0.033
b1	1.24	1.44	0.049	0.057
c	0.40	0.60	0.016	0.024
D	10.00	10.32	0.394	0.406
E	15.75	16.05	0.620	0.632
e	2.44	2.64	0.096	0.104
e1	4.88	5.28	0.192	0.208
F	3.10	3.5	0.122	0.138
L	13.50	13.90	0.531	0.547
L1	2.90	3.30	0.114	0.130
Φ	3.10	3.30	0.122	0.130

Marking Diagram



Ordering information

Model name	Package	Unit Weight	Base Quantity	Packing Quantity
YFW30P10AS	TO-263	0.04oz(1.16g)	800pcs/reel	1600pcs/box 8000pcs/Carton

Package Dimensions

TO-263

Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.30	4.70	0.169	0.185
A1	0.00	0.15	0.000	0.006
A2	4.30	4.55	0.169	0.179
B	1.10	1.50	0.043	0.059
b	0.70	0.90	0.028	0.035
b1	1.20	1.50	0.047	0.059
c	0.30	0.60	0.012	0.024
c1	1.17	1.37	0.046	0.054
D	9.90	10.20	0.390	0.402
E	8.50	8.90	0.335	0.350
e	2.44	2.64	0.096	0.104
e1	4.88	5.28	0.192	0.208
L	15.00	15.30	0.591	0.602
L1	5.20	5.40	0.205	0.213
L2	2.40	2.60	0.094	0.102
L3	1.60	1.80	0.063	0.071

Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.