


Surface Mount Automotive Transient Voltage Suppressors
4600watts/3600watts

V_{WM} : 10V~36V

V_{BR} :11.1~44.2V



FEATURES

- ♦ Ideally suited for load dump protection
- ♦ Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- ♦ High temperature stability due to unique oxide passivation and patented PAR® construction
- ♦ Integrally molded heatsink provides a very low thermal resistance for maximum heat dissipation
- ♦ Low leakage current at $T_J = 175^{\circ}\text{C}$
- ♦ High temperature soldering guaranteed: 260°C for 10 seconds at terminals
- ♦ Meets ISO7637-2 surge spec.
- ♦ Low forward voltage drop.

MECHANICAL DATA

- ♦ Case: DO-218AB
- ♦ Terminals: Plated, solderable per MIL-STD-750, Method 2026
- ♦ Approx. Weight: 2.58g / 0.091oz

Maximum Ratings and Electrical characteristics

Ratings at 25 ambient temperature unless otherwise specified.

Parameter		Symbol	Value	Unit
Peak pulse power dissipation with	10/1000 μs waveform	PPPM	4600	W
	10/10 000 μs waveform		3600	
Steady state power dissipation		P_D	6.0	W
Peak pulse current with a 10/1000 μs waveform (NOTE 1)		I_{PPM}	See Table 1	A
Peak forward surge current, 8.3ms single half sine-wave		I_{FSM}	600	V
Typical thermal resistance junction to case		$R_{\theta Jc}$	0.95	$^{\circ}\text{C/W}$
Operating junction and storage temperature range		T_J, T_{STG}	-55 to +175	$^{\circ}\text{C}$

NOTES:

1. Non-repetitive current pulse derated above $T_A=25^{\circ}\text{C}$

Electrical Characteristics

Part Number		V_R	$I_R @ V_R$		$V_{BR} @ I_T$		I_T	$V_C @ I_{pp}$	I_{pp}
Uni-polar	Bi-polar	V	$\mu A @ 25^{\circ}C$	$\mu A @ 175^{\circ}$	min(V)	max (V)	mA	V	A
SM6S10A	SM6S10CA	10.0	15	250	11.1	12.3	5	17.0	271
SM6S11A	SM6S11CA	11.0	10	150	12.2	13.5	5	18.2	253
SM6S12A	SM6S12CA	12.0	10	150	13.3	14.7	5	19.9	231
SM6S13A	SM6S13CA	13.0	10	150	14.4	15.9	5	21.5	214
SM6S14A	SM6S14CA	14.0	10	150	15.6	17.2	5	23.2	198
SM6S15A	SM6S15CA	15.0	10	150	16.7	18.5	5	24.4	189
SM6S16A	SM6S16CA	16.0	10	150	17.8	19.7	5	26.0	177
SM6S17A	SM6S17CA	17.0	10	150	18.9	20.9	5	27.6	167
SM6S18A	SM6S18CA	18.0	10	150	20.0	22.1	5	29.2	158
SM6S20A	SM6S20CA	20.0	10	150	22.2	24.5	5	32.4	142
SM6S22A	SM6S22CA	22.0	10	150	24.4	26.9	5	35.5	130
SM6S24A	SM6S24CA	24.0	10	150	26.7	29.5	5	38.9	118
SM6S26A	SM6S26CA	26.0	10	150	28.9	31.9	5	42.1	109
SM6S28A	SM6S28CA	28.0	10	150	31.1	34.4	5	45.4	101
SM6S30A	SM6S30CA	30.0	10	150	33.3	36.8	5	48.4	95
SM6S33A	SM6S33CA	33.0	10	150	36.7	40.6	5	53.3	86
SM6S36A	SM6S36CA	36.0	10	150	40.0	44.2	5	58.1	79

Note:

① For all types maximum $V_F = 2.0 V$ at $I_F = 100 A$ measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum。

②. Surge waveform: 10/1000 μs






V_R : Stand-off Voltage -- Maximum voltage that can be applied V_{BR} : Breakdown Voltage

V_C : Clamping Voltage -- Peak voltage measured across the suppressor at a specified I_{pp}

I_R : Reverse Leakage Current

I_T : Test current

Ratings and Characteristic Curves ($T_A = 25^\circ\text{C}$ unless otherwise noted)




Ordering information

Model name	Package	Unit Weight	Base Quantity
SM8SXXXA	TO-218AB	0.0914oz(2.59g)	500pcs/reel

Package Dimensions

TO-218AB

Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.8	5.8	0.189	0.228
B	13.3	13.7	0.524	0.539
C	1.7	2.3	0.067	0.091
D	8.3	8.7	0.327	0.343
d	2.3	3.1	0.091	0.122
G	0.5	0.7	0.020	0.028
H	4.9	5.2	0.193	0.205
h	2.5	3.9	0.098	0.154
I	8.7	9.3	0.343	0.366
J	9.7	10.3	0.382	0.406
W	9.5	10.5	0.374	0.414
S	1.5	2.5	0.059	0.099
L	15.0	16.0	0.591	0.630



Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.