

SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER

Reverse Voltage - 1000 V


Forward Current - 6.0A

FEATURES

- ◆High current capability
- ◆Low forward voltage drop
- ◆Glass Passivated Chip Junction
- ◆Designed for Surface Mount Application
- ◆Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

- ◆Case: TTF
- ◆Terminals: Solderable per MIL-STD-750, Method 2026
- ◆Approx. Weight: 0.461g /0.0163oz



Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	TTR610F	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS voltage	V_{RMS}	700	V
Maximum DC Blocking Voltage	V_{DC}	1000	V
Average Rectified Output Current at $T_c=100^{\circ}C$	I_o	6.0	A
Peak Forward Surge Current 8.3 ms Single Half Sine-Wave Superimposed on Rated Load(JEDEC method)	I_{FSM}	200	A
I^2t Rating for Fusing	I^2t	166	A ² S
Typical Thermal Resistance (Note1)	$R_{\theta JA}$	60	°C/W
	$R_{\theta JC}$	6	
	$R_{\theta JL}$	14	
Operating and Storage Temperature Range	T_j, T_{stg}	-55 ~ +150	°C

(1) Mounted on glass epoxy PC board with 4×1.5"×1.5" (3.81×3.81 cm) copper pad.

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Parameter	Symbols	Test Conditions	Typ	Max	Units
Instantaneous forward voltage	V_F	$I_F=6A, T_J=25^{\circ}C$	-	1.0	V
Reverse current at DC blocking voltage	I_R	$T_J=25^{\circ}C$ $T_J=125^{\circ}C$	-	1 200	uA
Maximum Reverse Recovery Time	T_{rr}	Measured with $I_F=0.5A, I_R=1A,$ $I_{rr}=0.25 A$	-	500	nS
Typical Junction Capacitance	C_j	$f=1MHz, V_R=4V$ DC $T_J=25^{\circ}C$	80	-	pF

Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current






Fig.6- Typical Transient Thermal Impedance



Marking Diagram



Ordering information


Package	Packing Description	Packing Quantity
TTF	Tape/Reel, 13" reel	3000PCS/Reel 30000PCS/Carton

Package Dimensions

TTF

Dim.	Millimeter(mm)		(mil)	
	Min.	Max.	Min.	Max.
A	1.35	1.75	53	68
C	0.25	0.55	9.8	21.6
D	9.4	9.8	370	385
E	8.4	8.8	330	346
E ₁	9.8	10.2	385	401
L	0.85	1.25	33	49
e	4.9	5.3	193	209
b	1.25	1.55	49	61
∠	10°			

The recommended mounting pad size



Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.