

8.0A Single-Phase GLass Passivated Fast Recovery Bridge Rectifiers

Reverse Voltage - 200 to 1000 V


Forward Current - 8.0 A

FEATURES

- ◆Glass passivated junction
- ◆The plastic material used carries Underwriters Laboratory flammability recognition 94V-0
- ◆Suge overload ratings to 200 amperes peak
- ◆Ideal for printed circuit board application
- ◆High temperature soldering guaranteed 265°C/10 seconds at 5 lbs(2.3kg)tension

MECHANICAL DATA

- ◆Case:HBS
- ◆Terminals:Platde leads solderable per MIL-STD-750, Method 2026
- ◆Polarity:Polarity symbols molded or Marked on body
- ◆Mounting Position:Any
- ◆Weight:0.015ounce,0.38 grams(approx)



Maximum Ratings & Thermal Characteristics

Rating at 25°C ambient temperature unless otherwise specified,Resistive or inductive load,60HZ. For Capacitive load derate current by 20%

Parameter		Symbol	RHBS802	RHBS804	RHBS806	RHBS808	RHBS810	unit
Maximum repetitive peak reverse voltage		V_{RRM}	200	400	600	800	1000	V
Maximum RMS bridge input voltage		V_{RMS}	140	280	420	560	700	V
Maximum DC blocking voltage		V_{DC}	200	400	600	800	1000	V
Maximum average forward rectified output current at $T_A=40^\circ C$		$I_{F(AV)}$	8.0					A
Max Instantaneous forward voltage drop per diode	$I_F=1.0A$	V_F	0.90					V
	$I_F=4.0A$		1.15					
	$I_F=8.0A$		1.30					
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)		I_{FSM}	200					A
Maximum DC reverse current at ratde $T_A=25^\circ C$ DC blocking voltage per element $T_A=125^\circ C$		I_R	5 100					μA
Rating for fusing($t<8.3ms$)		I^2t	166.0					A^2s
Maxumum reverse recovery time($I_F=0.5A,I_R=1.0A,I_{rr}=0.25A$)		T_{rr}	150		250		500	ns
Thermal resistance	Between Junction and Ambient	$R_{\theta JA}$	55					$^\circ C/W$
	Between Junction and Lead	$R_{\theta JL}$	14					
	Between Junction and Case	$R_{\theta JC}$	8					
Operating Junction Temperature Range		T_j	-55 ~ +150					$^\circ C$
Storage Temperature Range		T_{stg}	-55 ~ +150					$^\circ C$

Rating and Characteristic Curves

FIG.1-DERATING CURVE FOR OUTPUT RECTIFIED




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL REVERSE CHARACTERISTICS




FIG.4-TYPICAL FORWARD CHARACTERISTICS







FIG.5-Diagram of circuit and Testing wave form of reverse recovery time



Marking Diagram



Ordering information


Package	Packing Description	Packing Quantity
HBS	Tape/Reel, 13" reel	2500PCS/Reel 25000PCS/Carton

Package Dimensions

HBS

Dim.	Millimeter(mm)		Dimensions inInch	
	Min.	Max.	Min.	Max.
A	10.0	10.4	0.39	0.41
B	6.9	7.3	0.27	0.28
C	1.4	1.7	0.06	0.07
D	9.6	10.2	0.37	0.40
E	4.9	5.3	0.19	0.20
F	1.3	1.7	0.05	0.06

The recommended mounting pad size



Millimeter(mm)	
DIM	MIN
P0	5.10
P1	9.30
L	1.60
W	1.00

Disclaimer

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.