

Super Fast Recovery Rectifiers

Reverse Voltage - 600 V


Forward Current - 30 A

FEATURES

- ◆The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆Construction utilizes void-free molded plastic technique
- ◆Low reverse leakage
- ◆High forward surge current capability
- ◆High temperature soldering guaranteed
260°C/10 seconds at terminals

MECHANICAL DATA

- ◆Case : TO-247S/SPTS
- ◆Terminals : Solder plated, solderable per MIL-STD-750,Method 2026
- ◆Polarity : Polarity symbol marking on body
- ◆Mounting Position : Any



Primary Characteristic

I_F	2*15A
V_{RRM}	600V
I_{FSM}	200A
V_F	2.3V
T_J Max	150°C

Maximum Ratings (Per Leg) at Ta=25°C unless otherwise specified

Parameter		Symbols	Value	Units
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	600	V
Maximum RMS voltage		V_{RMS}	420	V
Maximum DC Blocking Voltage		V_{DC}	600	V
Average Forward Current	per device	I_F	30	A
	per diode		15	
Peak Forward Surge Current, 8.3ms Single Half Sine-wave		I_{FSM}	200	A
Operating Junction Temperature Range		T_J	-55 ~ +150	°C
Storage Temperature Range		T_{STG}	-55 ~ +150	°C
Typical Thermal Resistance		R_{θJC}	3.5	°C/W

Electrical Characteristics (Per Leg) unless otherwise specified

Characteristics		Symbols	Typ	Max	Units
Typical Forward Voltage at I _F =15A	TA=25°C	V _F	2.5	-	V
	TA=125°C		2.3	-	
Maximum Reverse Current at V _R =600V	TA=25°C	I _R	-	5	uA
	TA=125°C		-	500	uA
Maximum Reverse Recovery Time at IF=0.5A, IR=1A, IRR=0.25A		T _{RR}	-	50	nS

Note:1.Reverse recovery time test condition: I_F=0.5A I_R=1.0A I_{rr}=0.25A

RATINGS AND CHARACTERISTIC CURVES

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PERLEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS






FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS



Marking Diagram



Ordering information

Model name	Package	Unit Weight	Base Quantity	Packing Quantity
MUR3060SPTS	TO-247S	0.158oz(4.48g)	30pcs/tube	600PCS/Box 2400PCS/Carton

Package Dimensions

TO-247S

Dim.	Millimeter		Inches	
	Min.	Max.	Min.	Max.
E	15.40	15.80	0.60	0.62
D	19.50	20.50	0.77	0.80
S	5.30	5.50	0.21	0.22
ØR	4.50	5.50	0.18	0.22
ØP	3.40	3.80	0.13	0.15
L	14.0	14.5	0.55	0.57
L1	3.70	4.30	0.15	0.17
L2	18.5		0.73	
e	5.20	5.70	0.20	0.22
b	1.15	1.25	0.04	0.05
b1	1.80	2.20	0.07	0.09
b2	2.80	3.20	0.11	0.13
A	4.80	5.00	0.19	0.20
c	0.40	0.70	0.01	0.02
A1	2.30	2.45	0.09	0.10

Disclaimer

The information presented in this document is for reference only. Guangdong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.yfwdiode.com>, or consult YFW sales office for further assistance.